



FX1

FIX & GO

MS POLYMER
ADHESIVE &
SEALANT



FIXA[®]
CONSTRUCTION CHEMICALS



MS polymer based single component adhesive and sealant

- ✓ Fast curing and strong with high initial tack
- ✓ Hard elastic, solvent and isocyanate free



Quick & Easy to Use

- ✓ Rapid bonding
- ✓ High strength on initial grab
- ✓ Non slip
- ✓ Rapid curing
- ✓ Easy to apply
- ✓ Single component
- ✓ Can be applied on wet surfaces
- ✓ No primer required
- ✓ Paintable



Durable

- ✓ Resistant to UV - does not crack or yellow
- ✓ Keeps elasticity in low or high temperatures
- ✓ No shrinkage, sagging or peeling



Environmentally Friendly

- ✓ Solvent and isocyanate free
- ✓ Resistant to mould and fungus
- ✓ Odourless



→ Application

- ✓ Interior and exterior
- ✓ Rapid bonding on most materials
- ✓ Curtain tracks and roller blinds
- ✓ Wood and composite materials
- ✓ Ventilation systems
- ✓ Metals including aluminium, steel and stainless steel, anodised aluminium, brass and copper
- ✓ Bath, kitchen and all sanitary areas
- ✓ Natural materials such as marble, natural stone and granite

→ Technical Properties

Appearance	Density	Film Formation Time	Hardness (Shore A)	Tensile Strength
High viscosity MS paste	1,50 ± 0,05 g/cm ³	7 ± 3 minutes	65 ± 5	≥ 2.5 MPa (DIN 53504)
Curing Rate	Elongation at Break	Application Temperature	Service Temperature	
3 mm / 24 hours	> 150% (7 days)	Between +5°C / +35°C	-40°C / +80°C	